

Format bloczka	Wymiary (LxBxH)	Gęstość [g/cm <sup>3</sup> ]	Klasa odporności na ściskanie [N/mm <sup>2</sup> ]	Ilość bloczków na palecie [szt.]	Średnia waga bloczka [kg]	Przeciętna waga bloczków (z paletą)	Ilość palet na aucie	
	[mm]						Transport spedycja - max 24 t, auto bez HDS	Masa całkowita
U8L 	250x80x220	1,4	15	128	5,7	747	31	23 162
U12L 	250x120x220	1,6	15	96	9,4	917	26	23 852
U15L 	250x150x220	1,4	15	64	11,3	738	32	23 622
U18L 	250x180x220	1,4	15	64	13,5	879	27	23 733
		1,6	20		14,4	937	25	23 415
U18V 	250x180x220	1,8	20	64	16,6	1077	22	23 703
		1,8	25		16,7	1084	22	23 844
		2,0	30		19,6	1267	18	22 815
U24L 	250x240x220	1,4	15	48	18,1	884	27	23 863
		1,4	20		18,4	898	26	23 353
U24L(F) 	250x240x220	1,4	15	48	18,2	886	27	23 927
U24V 	250x240x220	1,8	20	48	22,4	1090	22	23 984
		1,8	25		22,7	1105	21	23 197
UPSW 	240x250x220	1,4	15	48	16,4	802	29	23 264
U12/2V	250x120x65	1,8	20	336	3,5	1174	20	23 484
U24/2V	250x240x98	1,8	20	108	10,7	1171	20	23 412